

# ELECTROMAGNETIC SOUND GENERATOR

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention:

5       The present invention relates to an electromagnetic sound generator, and more particularly to an electromagnetic sound generator that uses sound to indicate the operation of a directional indicator of a vehicle.

### 10    2. Description of the Related Art:

          The mode that is conventionally adopted for operating a directional indicator of a vehicle such as an automobile involves the use of a relay drive. In this mode, a drive current flows and flasher lamps light up  
15   each time the relay operates, and the driver can thus be notified of, and can check, the drive and operation of the directional indicator by means of the operation sound.

          In addition, Japanese Patent Laid-open No. 14195/98 discloses a vibration generator for notification for a  
20   device such as a portable communication device that is used to simultaneously generate vibration and sound to report an incoming call or report the time. Fig. 1 is a vertical section of the vibration generator for notification that is disclosed in Japanese Patent Laid-  
25   open No. 14195/98.

          Ring-shaped lower yoke 32 and upper yoke 31 are

10046198.01502

joined by way of magnet 30 inside a case that is made up  
by lower case 50 and upper case 51; coil 40 and bobbin 41  
that constitute first vibrator 11 are inserted in the  
space between lower yoke 32 and upper yoke 31; and bobbin  
5 41 is joined to disk-shaped second vibrator 21 for  
generating a notification sound.

Under control from conductor 60, this vibration  
generator realizes notification by means of vibration  
caused by the transmission of vibration to cases 50 and  
10 51 that results from first vibrator 11 striking against  
upper case 51 or lower yoke 32 or by the resilience of  
spring body 10; and realizes notification by means of  
sound caused by the transmission of sound waves to the  
outside from opening 52 that results from the vibration  
15 of second vibrator 21.

In recent years, however, the increased functions,  
miniaturization of control circuits, and higher  
automobile voltages in compact cars or luxury cars has  
complicated the adoption of the relay drive mode, which  
20 takes up space, in the directional indicator of an  
automobile, and the demand for the miniaturization of  
control circuits has brought about the necessity for  
replacing drive circuits of directional indicators with  
semiconductor circuits. When using drive circuits that  
25 employ semiconductor circuits, however, the driver of a  
vehicle can be kept aware of the operation of a

directional indicator only by means of a visual check of the front instrument panel, and the driver cannot be kept informed by sounds that were conventionally used.

Although the use of a buzzer or speaker can be  
5 considered as a means of using sound to keep a driver aware of the operation of a directional indicator, a buzzer emits only sound of a single frequency and thus differs from the operating sound of the prior art and may even be disconcerting to the driver; and although the use  
10 of a speaker enables production of a more complex sound, the drive circuit of the speaker may be complicated or the speaker body may be large and therefore entail the problems of increased use of space or higher costs.

In the vibration generator for notification that is  
15 disclosed in Japanese Patent Laid-open No. 014195/98, on the other hand, a yoke that is composed of ring-shaped lower yoke 32 and upper yoke 31 and a permanent magnet are provided inside a case composed of lower case 50 and upper case 51, vibrator 21 for generating sound being  
20 further provided. This invention therefore entails the problems of complicated construction, and further, difficulty in obtaining a desired sound effect.

#### SUMMARY OF THE INVENTION

25 It is an object of the present invention to provide an electromagnetic sound generator that can be easily and

inexpensively fabricated for generating an indication sound that can be used in vehicles or other environments.

It is another object of the present invention to provide an electromagnetic sound generator that generates  
5 sound that is similar to that of a relay of the prior art for keeping the driver of an automobile informed of the operation of a directional indicator, and that can be easily and inexpensively fabricated.

It is yet another object of the present invention  
10 to provide an electromagnetic sound generator that can keep the driver informed of the operation of a directional indicator though the use of a sound that does not vary from that of the prior art when the drive circuits of the directional indicator are converted to  
15 electronic circuits.

The electromagnetic sound generator of the present invention is made up by: a cup-shaped yoke; a spool on which a coil is wound that can be installed so as to contact the inside of the yoke; a spring having an edge  
20 that is secured to the edge of the yoke; a core having its lower surface secured to the central portion of the spring and that is movable up and down as a unit with the central portion of the spring; and a back plate that limits the displacement in the direction of the lower  
25 surface of the core; wherein attractive force causes the core to strike the yoke when current is conducted to the

coil, and the resilience of the spring causes the core to strike the back plate when current is cut off; thereby producing sound. In addition, the core has a projection for offsetting on its lower surface, and when the spring is secured to the lower surface of the core, the edge of the back plate is secured to the edge of the spring or to the edge of the yoke and the spring is pressed upward by the projection for offsetting of the core, whereby the spring is provided with pretension even without preparatory bending of the spring.

An electromagnetic sound generator according to another aspect of the present invention is made up by: a cup-shaped yoke; a spool on which a coil is wound that is installed so as to contact the inside of the yoke; a spring having an edge that is secured to the edge of the yoke and having at least one protrusion that protrudes from the edge toward the central portion; and a core having its lower surface secured to the central portion of the spring, that can move up and down as a unit with the central portion of the spring, and for which displacement in the direction of the lower surface is limited by the protrusion of the spring; wherein attractive force causes the core to strike the yoke when current is conducted to the coil, and the resilience of the spring causes the core to strike the protrusion of the spring when current is cut off; thereby producing

sound.

In addition, each of the above-described inventions may include coil terminals that are secured to the spool on which the coil is wound, that extend from the edges of the yoke and away from the yoke, and that serve the additional role of legs for self-support.

In addition, a single linear slit, a plurality of intersecting slits, or a plurality of slits that extend from the central portion toward the outer circumference may be provided on the upper surface of the yoke; a beam-like portion and lead-like portions that extend in both directions from this beam-like portion may also be provided on the upper surface of the yoke; and further, one or a plurality of vertical slits may also be provided in the side surfaces of the yoke.

The electromagnetic sound generator of the present invention is fabricated by inserting a spool, which is formed as a single unit with coil terminals by pressure-fitting or bonding, into the yoke; and then aligning in the same direction and inserting into the yoke the core and the spring, the core having been subjected to a notching or hole-opening process for preventing contact with the coil terminals that protrude from the yoke; and then welding the back plate to the edge of the yoke by a process such as resistance-welding or laser welding.

More specifically and as shown in Fig. 2 and Fig. 3,

the electromagnetic sound generator of the present invention is constituted by: cup-shaped yoke 1 that has been processed by deep drawing; spool 2 on which coil 3 is wound that is installed so as to contact the inside of yoke 1; round spring 5 having an edge welded to the rim of yoke 1 on the open end of yoke 1; core 4 that is welded to the central portion of round spring 5 and that is movable up and down as a unit with the central portion of round spring 5; coil terminals 6 that are secured to spool 2 on which coil 3 is wound by pressure-fitting or by insert molding and that serve the additional role of support legs for self-support; and back plate 7 that limits the displacement of core 4 in the downward direction; wherein core 4 strikes yoke 1 when current is conducted to coil 3 and core 4 and round spring 5 strike back plate 7 when current is cut off; thereby producing sound. The yoke, which constitutes a magnetic circuit, and the back plate, which limits the free vibration of the core that is attracted and then released, form portions of a case.

A spool on which a coil has been wound, a core that is movable up and down, and a spring are installed inside the cup-shaped yoke, and the conduction and cutting off of current to the coil causes the core to strike the yoke itself or on the spring side to generate a striking sound in accordance with the drive that comes in single beats.

10046198-01600  
The yoke, which constitutes the magnetic drive circuit,  
also serves as a sound generator, and the provision of  
openings such as slits in the upper surface and side  
surfaces of the cup-shaped yoke can enhance sound effects  
5 by causing variation in the tone, the sound volume, and  
the direction of the generated sound.

It is thus possible to generate a sound that  
resembles that of a relay-type directional indicator of  
an automobile, and a directional indicator sound for  
10 checking operation can be produced that is similar to a  
conventional indicator despite the use of electronic  
circuits for the directional indicator.

The above and other objects, features, and  
advantages of the present invention will become apparent  
15 from the following description based on the accompanying  
drawings, which illustrate an example of a preferred  
embodiment of the present invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is vertical section of a vibration generator  
for notification according to an example of the prior art.

Fig. 2A shows a front view of an electromagnetic  
sound generator of the present invention.

Fig. 2B shows a side view that includes a partial  
25 section of an electromagnetic sound generator of the  
present invention.



Fig. 2C shows a lower plan view of an electromagnetic sound generator of the present invention.

Fig. 3 is an exploded view for showing the construction of the electromagnetic sound generator of the embodiment shown in Fig. 2.

Fig. 4A and 4B is an upper plan view showing embodiments of openings that are provided in the upper surface of the yoke.

Fig. 5 shows an embodiment of openings that are provided in the upper surface of the yoke that are structured as leads.

Fig. 6 shows an embodiment of openings that are provided on the side surfaces of the yoke.

Fig. 7 shows an embodiment in which the yoke is fabricated by a pressing process.

Fig. 8 shows an embodiment in which the spring also serves as the back plate.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the electromagnetic sound generator of the present invention is next described in detail with reference to the accompanying figures.

We now refer to Fig. 2A, 2B, 2C and Fig. 3, in which are shown structural views showing an embodiment of the electromagnetic sound generator of the present invention, Fig. 3 being an exploded view showing the

construction of the present embodiment.

As shown in Fig. 3, the electromagnetic sound generator of this embodiment is made up by each of the components: cup-shaped yoke 1 that is composed of a magnetic material and that has a cylindrical portion, spool 2 on which coil 3 is wound, core 4, round spring 5, two coil terminals 6, and back plate 7.

Yoke 1 has a cup-shaped form that is formed by, for example, deep drawing; and spool 2, on which coil 3 is wound, has a through hole into which the body of core 4 is inserted, and further, has an outer circumference of a dimension that allows insertion of spool 2 such that spool 2 contacts the inner walls of the cylindrical portion of yoke 1. Coil terminals 6 have a prescribed width, the end portions on one side of coil terminals 6 having a form that is bent by pressing so as to allow electrical and mechanical contact with coil 3 that is wound on spool 2, and the end portions on the opposite side having sufficient length to extend as far as the exterior of yoke 1 when inserted into yoke 1 together with spool 2 and being made from a bendable material to serve the additional role of support legs for self-support of the electromagnetic sound generator.

Core 4 is constituted by: a core main body part that is inserted into the through hole of spool 2 and that can move up and down inside the through hole; and a

plate part that is provided on the end of the core main body, that has a diameter that is smaller than the diameter of the inner walls of the cylindrical portion of yoke 1, and that has notches that allow the end portions  
5 of coil terminal 6 to pass through toward the exterior of yoke 1.

Round spring 5 is in an approximately H-shaped form, and more specifically, is an elastomer of monolithic construction having a Z shape that is made up by two arc-  
10 shaped outer portions and a central portion that joins these arc-shaped portions; the end portions of coil terminals 6 being able to pass between the two arc-shaped outer portions and toward the exterior of yoke 1; the center of the central portion being welded to the center  
15 of the plate part of core 4; and the edge portion of round spring 5 being shaped to allow welding to the rim of the opening of the cylindrical shape of yoke 1. In addition, round spring 5 is treated with a preparatory bending such that the central portion of round spring 5  
20 that is welded to core 4 displaces core 4 in the direction of the lower surface, the provision of this pretension in advance being appropriate for preventing the generation of noise by, for example, vibration.

Finally, back plate 7 has notches through which the  
25 end portions of coil terminals 6 pass to the exterior of yoke 1, and is constituted in a shape and by a material

that can limit the downward displacement of the plate part of core 4 and round spring 5.

As shown in Fig. 2A, 2B, and 2C the main body part of core 4 is inserted into the through hole inside spool 2 such that core 4 is able to move up and down and has a length such that the plate part of the lower portion of core 4 does not contact the lower surface of spool 2 even when the upper portion of core 4 contacts the ceiling of yoke 1. In addition, as described in the foregoing explanation, the plate part of the lower portion of core 4 is of a shape in which portions are notched to prevent contact with coil terminals 6. Furthermore, the side surface of the plate part of the lower portion of core 4 in areas that are not notched confronts the side surface inside yoke 1 such that spacing between the two surfaces is kept uniform and the two surfaces do not rub against each other despite up and down movement of core 4; and further, core 4 has a shape and a structure that is supported by spring 5 such that the magnetic reluctance of this side surface does not vary.

As described hereinabove, a spring is used that is constructed in a Z shape such that round spring 5 does not contact coil terminals 6, but an X shape, an H shape, a whorl shape, or a plate shape may also be considered in addition to the Z shape. Similarly, back plate 7 may be formed in an H shape or in a shape with notches in the

longitudinal direction at two points so as not to contact coil terminals 6.

Furthermore, instead of providing spring 5 with pretension as described hereinabove, a configuration may also be considered in which: a projection for offsetting is made on the lower surface of core 4, this projection is passed through a hole that is provided in spring 5 in the portion for securing to spring 5 so as to project from the provided hole, spring 5 and the lower surface of core 4 are secured, and when the edge of spring 5 and the edge of back plate 7 are secured to yoke 1, the projection for offsetting on core 4 that contacts back plate 7 pushes up the central portion of spring 5, thereby providing spring 5 with pretension without the preparatory bending. Taking this pretension into consideration can prevent erroneous operation due to outside disturbances such as vibration. The configuration for securing a spring and a core having a projection can be modified as appropriate according to each form.

Explanation next regards the method of fabricating the electromagnetic sound generator of this embodiment. The electromagnetic sound generator of this embodiment can be fabricated by assembly that uses yoke 1 as a base, wherein the components such as spool 2, core 4, spring 5, and back plate 7 are inserted from one direction into yoke 1 as shown in Fig. 3.

For example, coil terminals 6 are pressed into  
spool 2, spool 2 on which coil 3 is wound is inserted  
inside yoke 1 and bonded or snap-fitted to the inner  
walls of yoke 1 to secure spool 2 to yoke 1, core 4 and  
5 spring 5 are secured in advance at their central portions  
by resistance welding or laser welding and then inserted  
inside yoke 1, the edge portion of spring 5 is secured to  
the edge portion of yoke 1 at several points by a similar  
welding means, and the edge portion of back plate 7 is  
10 similarly secured over spring 5 at several points. At  
this time, coil terminals 6 extend straight downward from  
spool 2, and core 4, spring 5, and back plate 7 are  
constructed so as to allow easy installation as  
structures that avoid these coil terminals 6. After core  
15 4, spring 5, and back plate 7 have been installed and  
secured, the lower end portions of coil terminals 6 are  
bent in a horizontal direction to serve the additional  
role of legs for self support of the electromagnetic  
sound generator. Although the explanation in Fig. 3  
20 assumes the use of surface-mounted components,  
fabrication may be similarly realized with components  
that are inserted into through-holes.

The ability to employ an easy fabrication method  
such as described above allows the present invention to  
25 be manufactured at low cost, and this fabrication method  
is also easily amenable to automation.

209170-8574007

Explanation next regards the operation of the electromagnetic sound generator of this embodiment. When coil 3 is energized, the magnetomotive force that is generated in coil 3 causes magnetic flux to flow through the closed magnetic circuit that is constituted by core 4 and yoke 1, whereupon core 4 is attracted toward the upper portion of yoke 1 and strikes the upper surface of yoke 1 to produce sound. When the current to coil 3 is cut off, the magnetic flux disappears in the closed magnetic circuit that is constituted by core 4 and yoke 1, and under the resilience of spring 5, core 4 and spring 5 strike back plate 7 to produce sound. Sound is thus generated in single beats both upon supplying and cutting off current.

15       The relay-operated sound that is produced when operating a directional indicator of the prior art is generated by the collision of magnetic metal components, i.e., armature and core or by the collision between contacts, and a similar sound is obtained by the sound generator of this embodiment because the sound is produced by collision between magnetic metal components, i.e., the yoke and core.

Explanation next regards another embodiment. In the above-described embodiment, an example was described in which the shape and structure of yoke 1 that constitutes a portion of the electromagnetic sound generator was a

cup-shaped component, i.e., a cylinder having an open side and a closed side. However, the provision of openings or a form that allows vibration of appropriate shape on the surface of the closed side of the yoke or in the side surfaces of the cylinder enables setting of the amount of diffusion, the direction of diffusion, and the tone of the sound and can realize desired sound effects.

Fig. 4A, 4B, and 4C shows embodiments for providing openings in the upper surface of yoke 1. Fig. 4A is an example in which an opening is provided in slit form on the upper surface, the sound that is produced by striking of core 4 being spread to the outside by way of this slit. This configuration not only improves the tone of the striking sound but enables sufficient diffusion of the sound and increases sound pressure in a prescribed direction. Providing slits of this type at equal intervals can unify the frequency of oscillation of the plate springs that are formed between the slits on the upper surface of the yoke and thus enable an increase in the sound pressure of a specific frequency.

Fig. 4B and 4C show slits that have been formed in a cross shape and in a partial radiating pattern. The striking of core 4 causes the free end portions that are formed on the upper plane of yoke 1 by the slits to vibrate, and tone effects can be provided according to the shapes that are shown in Fig. 4B and 4C.



Fig. 5 shows a form in which a plurality of lead structures has been employed to make the opening a vibrator structure. The opening in the upper surface forms a beam part and a plurality of lead-shaped parts of differing lengths and having free ends, and the vibration produced by the striking of the core enables resonance of the leads and can produce tone effects.

Fig. 6 shows an embodiment in which openings are provided in the cylindrical part of yoke 1. The formation of slits as openings in the axial direction in the cylindrical part enables an addition to the sound diffusion level, the direction of diffusion, and the tone effects similar to the above-described case. In the present embodiment, yoke 1 is provided as a slit form, and the adoption of a form that allows vibration enables resonance with the vibration that is produced inside to enable the production of desired sound effects.

As described in the foregoing explanation, various sound effects can be produced, for example, producing sounds of a variety of frequencies, by providing openings that are a desired number of slits at equal intervals or at unequal intervals in the upper surface or side surfaces of the yoke, or by using an opening to form both a cantilevered beam or a beam that is supported at both ends and, using this beam as a base, leads that are constituted by cantilevered beams extending to the right

and left of the base beam.

Although an example in which a plate was fabricated by deep drawing was used in the description of a method of fabricating yoke 1 that constitutes a portion of the electromagnetic sound generator in the above-described embodiment, the yoke may also be fabricated by a pressing process. Fig. 7 shows an example for a case in which yoke 1 is fabricated by means of a pressing process. As shown in Fig. 7, a metal part may be formed in the developed shape of a polyhedron, such as in a cross shape, and a polyhedron cup-shaped yoke may then formed from this metal part. Depending on the developed shape of the metal part, yokes of different shapes such as cylindrical shapes may also be produced.

Fig. 8 shows yet another embodiment. This embodiment enables the combination of the spring and back plate to simplify the construction. This embodiment is of a structure in which stoppers 8 are formed at positions that do not interfere with the flexibility of a Z-shaped spring and in which the movement of core 4 can be limited by stoppers 8 when the core that has been attracted upward returns under the resilience of the spring.

The electromagnetic sound generator of the present invention: is constructed by installing, inside a cup-shaped yoke, a spool on which a coil is wound, a core that is movable up and down, a spring, and a back plate

that limits the free vibration of the released core; has  
a simple construction in which the yoke and back plate  
form at least a portion of the case; allows for easy  
assembly and fabrication of each component; and enables  
5 manufacture that is both inexpensive and easily amenable  
to automation.

In the electromagnetic sound generator of the  
present invention, energizing the coil causes the core to  
be attracted and strike the upper surface of the yoke  
10 itself, which forms a magnetic circuit; and cutting off  
current to the coil causes the core that has been  
attracted to be released and strike either the spring  
itself or a back plate that limits the free vibration,  
whereby a striking sound is produced by single beats in  
15 accordance with the drive and a sound generator mechanism  
is realized by a minimum number of components.

In the present invention, moreover, the cup-shaped  
yoke, which is a magnetic circuit for driving, also  
serves as a sound generating part, and using the  
20 resonance characteristics of the yoke itself, and further,  
providing openings that form slits or leads in the upper  
surface and side surfaces of the cup shape enables the  
enhancement of desired sound effects such as the tone,  
sound volume, and direction of emitted sound.

25 The present invention enables the generation of a  
sound that resembles that of relay-mode directional

indicators for automobiles, and further, enables the generation of a directional indicator sound for checking operation that is similar to that of conventional relay-mode devices when a directional indicator is converted to  
5 electronic circuits.

It is to be understood, however, that although characteristics and advantages of the present invention have been set forth in the foregoing description, the disclosure is illustrative only, and changes may be made  
10 in the arrangement of the parts within the scope of the appended claims.